



Gas Oil:

Property	Unit	Min.	Max.	Method
DISTILLATION:				ASTM D-86
90% RECOVERED	°C		357	
DENSITY @ 15 °C	Mg/MI.	0.820	0.870	ASTM D-1298
COLOR	ASTM		2.5	ASTM D-1500
TOTAL SULFUR	%Wt.		1.2	ASTM D-1266
FLASH POINT P.M.	°C	55		ASTM D-93
Kinematic Viscosity@ 40 °C	CSt.	1.9	5	ASTM D-445
POUR POINT	°C		-6	ASTM D-97
CORROSION, COOPER, CLASSIFICATION			1	ASTM D-130
CARBON RESIDUE ON 10% RESIDUE	%Wt.		0.1	ASTM D-189
TOTAL ACID NUMBER	Mg. KOH/Gr.		1	ASTM D-974
STRONG ACID NUMBER	Mg .KOH/Gr.		NIL	ASTM D-974
ASH	%Wt.		0.01	ASTM D-482
WATER BY DISTILLATION	%Vol.		0.05	ASTM D-95
SEDIMENT BY EXTRACTION	%Wt.		0.01	ASTM D-473
DIESEL INDEX		50		IP - 21
CETANE INDEX		46		ASTM D-9760 OR D-4737